

ImagePerfect™ 2554 Plus

Clear Gloss Polymeric Vinyl (FR)

ImagePerfect™ 2554 Plus is a clear gloss polymeric vinyl with a permanent adhesive for indoor and outdoor applications. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

ImagePerfect™ 2554 Plus Clear Gloss Polymeric Vinyl is a permanent product for indoor and outdoor applications such as markings, decorations and vehicle graphics. It promotes high levels of print quality with remarkable text definition and a large colour gamut to ensure colourful images with vibrant area infills. It is equipped with a backing paper that offers excellent lay flat properties and it utilises an adhesive system that performs well in areas of high altitude and at cold temperatures. It should be applied at temperatures greater than +5°C. Laminate: IP 2810-103, IP 2810-202, IP 2830-106, IP 2830-109, IP 2830-200, etc.

Attention: Please make sure the printed IP 2554 Plus is completely dry before laminating. Before the IP 2554 Plus is applied, the surface should be completely cleaned. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match component cleaning solution to ensure that the surface is dry and free of dust and grease.

Specifications	
Description	Polymeric vinyl
Colour	Clear gloss
Thickness	70mym
Weight	N/A
Adhesive	Advanced acrylic, permanent
Adhesive Strength	18N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m ²
Temperature Range	-30°C to +90°C
Durability (unprinted)	7 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.